

Safety Data Sheet

Cyntrol® 2045

SDS Number: 197C Revision: February 24, 2023

Section 1: IDENTIFICATION

1.1 Product Name: Cyntrol® 2045

1.2 Other Identification:

Chemical Family: Inorganic salt solution

Formula: $(NH_4)_2S_x$

1.3 Recommended Use of Chemical: Cyanide assisted corrosion control for petroleum industry

1.4 Manufacturer: Tessenderlo Kerley, Inc.

2910 N. 44th Street, Suite 100 Phoenix, Arizona 85018

Information: (602) 889-8300

1.5 Emergency Contact: Tessenderlo Kerley, Inc.: (800) 877-1737

CHEMTREC: (800) 424-9300 (Domestic)

(703) 527-3887 (International)

Section 2: HAZARD(S) IDENTIFICATION

2.1 Hazard Classification: Health Acute Oral Toxicity Category 3

Acute Inhalation Toxicity Category 3
Skin Corrosion/Irritation Category 1B
Eye Damage/Irritation Category 1

Physical None

2.2 Signal Word: Danger

2.3 Hazard Statement(s): Toxic if swallowed.

Toxic if inhaled.

Causes serious burns and eye damage.

Causes serious eye damage.







2.4 Symbol(s):

2.5 Precautionary Statement(s):

If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center/doctor/regional medical center.

If on skin (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower. Immediately call poison

center/doctor/regional medical center. Wash contaminated clothing before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call poison center/doctor/regional medical center.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call poison center/doctor/regional medical center.

Wash hands and face thoroughly after handling. Do not eat, drink or smoke when using this product.

Avoid breathing fumes/gas/mist/vapors/spray.

Wear neoprene rubber gloves, chemical suit, boots, chemical goggles and full-face shield.

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Use only outdoors or in a well-ventilated area.

Dispose of contents/container to chemical waste facility in accordance with local/state/federal regulations.

Do not allow release to aquatic waterways.

2.6 Unclassified Hazard(s): Aquatic toxicity

2.7 Unknown Toxicity Ingredient: None

Section 3: COMPOSITION/INFORMATION on INGREDIENTS

3.1 Chemical Ingredients: (See Section 8 for exposure guidelines)

Chemical	Synonym Common Name	CAS No.	EINECS No.	% by Wt.
Diammonium polysulfide	Ammonium polysulfide	12259-92-6	235-512-5	55
Ammonium hydroxide	Aqua ammonia	1336-21-6	215-647-6	31
Water	Water	7732-18-5	231-791-2	Remaining %

Section 4: FIRST AID MEASURES

4.1 Symptoms/Effects:

Acute: Skin contact will cause skin corrosion. Eye contact will cause irritation/damage. Inhalation of

product vapors will cause severe respiratory problems. Oral exposure will cause burns of mouth

and throat.

Chronic: No known chronic effects.

4.2 Eyes: Immediately flush with large quantities of water for 15 minutes. Hold eyelids open during

irrigation to ensure thorough flushing of the entire area of the eye and lids. Get immediate medical attention.

4.3 Skin: Immediately flush with large quantities of water. Remove contaminated clothing under a

safety shower. Continue rinsing. Get immediate medical attention.

4.4 Ingestion: DO NOT INDUCE VOMITING. Give 2-4 glasses of water. If vomiting should occur, repeat fluid

administration. Get immediate medical attention.

4.5 Inhalation: Remove victim from contaminated atmosphere. If breathing is labored, administer Oxygen.

If breathing has ceased, clear airway and start CPR. Get immediate medical attention.

Section 5: FIRE FIGHTING MEASURES

5.1 Flammable Properties:

NFPA: Health - 3 Flammability - 1 Reactivity - 1

5.2 Extinguishing Media:

5.2.1 Suitable Extinguishing Media: Not flammable, use media suitable for combustibles involved in

fire.

5.2.2 Unsuitable Extinguishing Media: None known.

5.3 Protection of Firefighters:

5.3.1 Specific Hazards Arising from the Chemical:

Liquid is corrosive to skin and eyes. Vapors of Ammonia and small amounts of Hydrogen sulfide exist in the vapor space over the liquid. Heating this product will evolve vapors of Ammonia and Hydrogen sulfide. Both of these vapors are very toxic and

may form flammable mixtures with air.

Physical Hazards: Heating (flames) of closed or sealed containers may cause violent

rupture of the container due to thermal expansion of compressed

gases.

Chemical Hazards: Dilution with water will increase the evolution of Hydrogen

sulfide vapors.

5.3.2 Protective Equipment and Precautions for Firefighters:

Firefighters should wear self-contained breathing apparatus

(SCBA) and full fire-fighting turnout gear. Keep

containers/storage vessels in fire area cooled with water spray.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions:Use personal protective equipment specified in Section 8. Isolate

the release area and deny entry to unnecessary, unprotected and

untrained personnel.

6.2 Environmental Precautions: Keep out of "waters of the United States" because of aquatic

toxicity (See Section 12).

6.3 Methods of Containment:

Small Release: Confine and absorb small releases with sand, earth or other inert

absorbents.

Large Release: Shut off release, if safe to do so. Dike spill area with earth, sand

or other inert absorbents to prevent runoff into surface waterways (aquatic toxicity), storm drains or sewers.

6.4 Method for Cleanup:

Small Release: Spray release area with weak (3-5%) solution of Hydrogen

peroxide to limit the release of Hydrogen sulfide and Ammonia vapors. Shovel up contaminated area and place in plastic drums

for proper waste disposal. Use non-sparking tools.

Large Release: Recover as much of spilled product as possible using an air-

operated diaphragm pump, hoses and non-sparking tools. Use recovered product as originally intended or dispose of as a chemical waste. Treat remaining material as a small release

(above).

Section 7: HANDLING and STORAGE

7.1 Handling: Avoid contact with skin and eyes. Use only in a well-ventilated area. Wash thoroughly after

handling product. Avoid breathing product vapors.

7.2 Storage: Store in cool, dry well-ventilated areas. Do not store combustibles or incompatible materials in

product storage areas or loading/unloading areas. Keep away from heat or flames. Storage in drums or totes is not recommended due to possible product degradation if containers are not properly handled and are allowed to overheat or come in contact with incompatible

materials. Product degradation can cause toxic gas release. (See Section 10.5, for materials of

construction)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Guidelines:

Chemical	OSHA PELs		ACGIH TLVs	
	TWA	STEL	TWA	STEL

Ammonia	50 ppm	None	25 ppm	35 ppm
Hydrogen sulfide	None	20 ppm (Ceiling)	1 ppm	5 ppm
Diammonium polysulfide	None	None	None	None
Ammonium hydroxide	None	None	None	None
Water	None	None	None	None

8.2 Engineering Controls:Use adequate exhaust ventilation to prevent inhalation of product

vapors. Keep eye wash/safety showers in areas where product is

commonly handled.

8.3 Personal Protective Equipment (PPE):

8.3.1 Eye/Face Protection: Chemical goggles and a full face shield.

8.3.2 Skin Protection: Neoprene rubber gloves, boots and chemical suit should be worn to

prevent contact with the liquid. Wash contaminated clothing prior to

reuse.

8.3.3 Respiratory Protection: Respiratory protection is based on potential for exposure to Ammonia

vapors and to a lesser degree Hydrogen sulfide. Both of these vapors exist in the vapor space over the liquid. Respiratory protection is recommended when connecting or disconnecting hoses to transfer product solutions between containers. Respiratory protection may consist of SCBA, pressure demand, (MSHA or NIOSH approved or

equivalent), or an air-supplied respirator with full face mask or a full face

mask with appropriate cartridges.

8.3.4 Hygiene Considerations: Common good industrial hygiene practices should be followed, such as

washing thoroughly after handling and before eating or drinking.

Section 9: PHYSICAL and CHEMICAL PROPERTIES

9.1 Appearance:Ruby-red, liquid9.2 Odor:Strong ammonia odor9.3 Odor Threshold:37 ppb (ammonia)

4.7 ppb (hydrogen sulfide)

9.4 pH: 10.8 to 11.5

9.5 Melting Point/Freezing Point: 0° to 32°F (-17.8° to 0°C)

9.6 Boiling Point: 100°F (38°C)
9.7 Flash Point: Not determined
9.8 Evaporation Rate: Not determined
9.9 Flammability: Not applicable

9.10 Upper/Lower Flammability Limits: 15 to 28%, in air (ammonia)

9.11 Vapor Pressure: 314 mm Hg (41.9 kPa) @ 70°F (21.1°C)

9.12 Vapor Density: Not determined

9.13 Relative Density: 1.15 to 1.18 (9.6 to 9.8 lbs/gal)

9.14 Solubility: Completely soluble with precipitation of elemental sulfur.

9.15 Partition Coefficient: No data available.9.16 Auto-ignition Temperature: Not applicable

9.17 Decomposition Temperature: Not determined9.18 Viscosity: Not determined

Section 10: STABILITY and REACTIVITY

10.1 Reactivity: Interaction with strong oxidizers or acidic or alkaline materials.

10.2 Chemical Stability:This product is stable under normal (ambient) temperature and

pressure.

10.3 Possibility of Hazardous Reactions: Contact with acids or acidic materials will cause a significant

increase in highly toxic Hydrogen sulfide vapors being released.

10.4 Conditions to Avoid: High temperatures and fire conditions.

10.5 Incompatible Materials: Strong oxidizers such as nitrates, nitrites or chlorates can cause

explosive mixtures, if heated to dryness. Acids will cause the release of Hydrogen sulfide, a highly toxic gas. Alkalies will accelerate the evolution of Ammonia. Ammonium solutions are not compatible with Copper, Zinc or their alloys (i.e. bronze, brass, galvanized metals, etc.). These materials of construction should not be used in handling systems or storage containers for

this product.

10.6 Hazardous Decomposition Products: Heating this product will evolve Ammonia vapors. As the pH of

the solution decreases, Hydrogen sulfide vapors will increase significantly. Continued heating will cause Oxides of Nitrogen and

Sulfur to be released.

Section 11: TOXICOLOGICAL INFORMATION

11.1 Oral: Oral-Rat LD₅₀: 152 mg/kg (ammonium polysulfide)

Oral-Rat LD₅₀: 350 mg/kg (ammonium hydroxide)

11.2 Dermal: Skin Rabbit LD₅₀: 1,790 mg/kg (ammonium polysulfide)

11.3 Inhalation: INH-Rat LC₅₀: 2,000 ppm, 4 hours (ammonia)

INH-Rat LC₅₀: 444 ppm (hydrogen sulfide)

11.4 Eyes: No data available.

11.5 Chronic/Carcinogenicity: Not listed in NTP, IARC or by OSHA.

11.6 Teratology: No data available.

11.7 Reproduction: No data available.

11.8 Mutagenicity:No data available.

Section 12: ECOLOGICAL INFORMATION

12.1 Ecotoxicity:No data available, however this is a strong Ammonia solution and

Ammonia solutions are typically detrimental to the aquatic

environment.

12.2 Persistence & Degradability:No data available.

12.3 Bioaccumulative Potential: This product is not bioaccumulative.

12.4 Mobility in Soil: No data available.

12.5 Other Adverse Effects: None

Section 13: DISPOSAL CONSIDERATIONS

Consult federal, state and local regulations for disposal requirements.

Section 14: TRANSPORT INFORMATION

14.1 Basic Shipping Description:

14.1.1 Proper Shipping Name: Ammonium polysulfide, solution

14.1.2 Hazard Classes:8, 6.114.1.3 Identification Number:UN281814.1.4 Packing Group:III

14.1.5 Hazardous Substance: No, however a 333 gallon release would exceed the

ammonium hydroxide RQ of 1,000 lbs.

14.1.6 Marine Pollutant: No

14.2 Additional Information:

14.2.1 Other DOT Requirements:

14.2.1.1 Reportable Quantity: No (See Section 14.1.5, above).

14.2.1.2 Placard(s):Corrosive **14.2.1.3 Label(s):**Corrosive, Toxic

14.2.2 USCG Classification: No data available.

14.2.3 International Transportation:

14.2.3.1 IMO:Ammonium polysulphide solution14.2.3.2 IATA:Ammonium polysulphide solution14.2.3.3 TDG (Canada):Ammonium polysulphide solution14.2.3.4 ADR (Europe):Ammonium polysulphide solution14.2.3.5 ADG (Australia):Ammonium polysulphide solution

14.2.4 Emergency Response Guide: 154

14.2.5 ERAP - Canada: Not applicable

14.2.6 Special Precautions: Not applicable

Section 15: REGULATORY INFORMATION

15.1 U.S. Federal Regulations:

15.1.1 OSHA: This product is considered hazardous under the criteria of the

Federal OSHA Hazard Communication Standard (29 CFR

1910.1200).

15.1.2 TSCA: Product is contained in USEPA TSCA Inventory.

15.1.3 CERCLA: Reportable Quantity – No, (See Section 14.1.5, above).

15.1.4 SARA Title III:

15.1.4.1 Extremely Hazardous Substance (EHS): No

15.1.4.2 Section 312 (Tier II) Ratings: Immediate (acute) Yes

Fire Yes
Sudden Release No
Reactivity Yes
Delayed (chronic) No

15.1.4.3 Section 313 (FORM R): Yes, ammonia solution.

15.1.5 RCRA: Possible D003 hazardous waste.

15.1.6 CAA (Hazardous Air Pollutant/HAP): Not applicable

15.2 International Regulations:

15.2.1 Canada:

15.2.1.1 WHMIS: E, D2B

15.2.1.2 DSL/NDSL: On DSL Inventory, #9757

15.3 State Regulations:

benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to

www.P65.Warnings.ca.gov.

Section 16: OTHER INFORMATION

REVISIONS:

This SDS was reformatted to comply with the new Hazard Communication Standard dated March 26, 2012, by the Regulatory Affairs Department of Tessenderlo Kerley, Inc. 2/9/2015.

Revised Section 2 Precautionary Statements. 4/14/2015; Revised sections 1, 2, 3, 8, 10, 11 and 15. 6/10/2016; Revised section 15. 8/6/2018; Revised Section 1. 1/3/2020; Revised logo. 10/4/2021; Revised Section 7.2. 2/24/2023

The information above is believed to be accurate and represents the best information currently available to Tessenderlo Kerley, Inc. (TKI). No warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product, or the hazards related to its use. Users should make their own investigations to determine the suitability of the information for their particular purpose and on the condition that they assume the risk of their use thereof. TKI reserves the right to revise this Safety Data Sheet periodically as new information becomes available.